



|| 25 kVAr

Three-phase cylindrical capacitors Nitrogen (N2) Gas filled

Code	MKPG25400
Rated Voltage	400 ÷ 440 V
Rated Frequency	50 Hz
Capacitors Voltage	440 V
Capacitors Voltage max 8h/day	485 V
THDi max	≤ 25 %
THDc	80 %
Power @ 400 V	25 kvar
Power @ 415 V	26.75 kvar
Power @ 440 V	30.25 kvar
Capacitance	3x166 uF
Capacitance tolerance	-5...+10 %
Power dissipation	0,25 W/kVAr
UTT	1035 V rms / 2 sec.
UTC	3,6 kV rms / 2 sec.
Protection Degree	IP20
Humidity class	C
Temperature class	-50/C
Reference standards	IEC60831-1/2, VDE0560-46/47 UL N.810 CSA C22 N.2

	Vmax	24h	8h	30m	15m	5m	1m	Peak
		440	510	520	530	575	575	1350
		3In		4In	5In			10 In



Construction features

Self-healing metallized polypropylene film.

Housing in cylindrical aluminum box, hermetically sealed. Overpressure safety device. IP20 terminals with terminal board.

The gas insulation, thanks to the characteristics of the Nitrogen (N2), a "free humidity Gas" (dry type) exacerbates any possible infiltration of air inside the cylinder which, following an electrical discharge, would cause the fault of Capacitor.

Furthermore, Nitrogen is a non-flammable gas and therefore the use of this type, even in case of breakage, would not result in a fire risk..

Expected life

>150.000 ore

Installation

Horizontal / Vertical

Dimensions (WxH)

D1

95 ± 1 mm

D2

99.7 ± 0.5 mm

L1

280 ± 2

L2

32 + 5 / -2 mm

LB

16 + 1 mm

GB

M12

a

39 ± 1 mm

b

45.5 ± 1 mm

Weight

2,0 Kg

