

# g48filter-fix

**>>>3-years warranty****25 kvar at 400 V 50 Hz**

<b>Code</b>	<b>FFTG4825</b>
<b>Rated Voltage</b>	400 ÷ 415 V ± 10%
<b>Rated Frequency</b>	50 Hz
<b>Capacitors Voltage</b>	480 V
<b>THDi max</b>	100 %
<b>THDv max</b>	≤ 6 %
<b>Power (400 V)</b>	25 kvar
<b>Rated Current</b>	36 A
<b>Temperature class</b>	-5 / +52°C
<b>Insulating Voltage</b>	690 V
<b>Max overcurrent</b>	1,3 In
<b>Total losses</b>	< 4 W/kvar
<b>Reference standards</b>	EN61921, EN61439-1

**Capacitors**

Three-phase metallized polypropylene Capacitors with **Nitrogen Gas (N2) insulation** "dry type", MKPG Series, Rated Voltage 480 V, Operating Voltage 400 V, Insulation Voltage 690 V, equipped with discharge resistors, overpressure safety device and IP20 terminals. Dielectric losses < 0,2W/kVAr. Reference Standards IEC60831-1/2, UL N.810, CSA

Overvoltage: 480 V (24h), 530 V (8h), 555 V (30m), 585 V (5m), 625 V (1m), 1450 V (Picco)

Overcurrent: 3In (24h), 4In (30m), 5In (15m), 10In (Picco)

**Detuning Reactors**

Detuning reactors made of sheet oriented crystals, placed in series between the contactor and the capacitor bank, with the following features: linearity 1.8 Ip/In, realized in class H, over temperature range: 60°C, complete with thermal probe for switching off Capacitors Banks in case of overtemperature, limit the peak current inrush capacitors, detuning frequency 189 Hz (p=7%), standard for 5th Harmonic

**Switch Disconnecter**

N. 1 Switch Disconnectors with door interlock sized 1,5 time the nominal current of PFC Unit as per EN61921, 3\*80 A

**Fuses**

NH00 Fuses 100 kA for the protection of each capacitor bank. Auxiliary circuits are protected through 10,3 x 38 Fuses

**Cabinet**

Sheet-steel enclosure 15 and 20/10, painted with epoxy dust paint, colour RAL7035 (others on request).

Protection degree IP30 external, IP00 internal (IP20 with open doors on live parts).

Internal wiring made with cables are FS17 type, Reference standards CEI EN 50575, CEI UNEL 35716, CEI EN 50525 e CPR UE305/11.),

<b>Incoming cables</b>	From the Top
<b>Dimensions / Weight</b>	(W*H*D) 362*642*262 mm / 46 Kg
<b>Ventilation</b>	Ventilation Natural