

# r46fix

## 15 kvar at 400 V 50 Hz

<b>Code</b>	<b>FTR4615</b>
<b>Rated Voltage</b>	400 ÷ 415 V ± 10%
<b>Rated Frequency</b>	50 Hz
<b>Capacitors Voltage</b>	460 V
<b>THDi max</b>	≤ 19%
<b>Power (400 V)</b>	15 kvar
<b>Rated Current</b>	22 A
<b>Temperature class</b>	-5 / +52°C
<b>Insulating Voltage</b>	690 V
<b>Max overcurrent</b>	1,3 In
<b>Total losses</b>	< 2 W/kvar
<b>Reference standards</b>	EN61921, EN61439-1



### Capacitors

Three-phase metallized polypropylene Capacitors with Oil, "dry type", MKPR Series, Rated Voltage 460 V, Operating Voltage 400 V, Insulation Voltage 690 V, equipped with discharge resistors, overpressure safety device and IP20 terminals. Dielectric losses < 0,2W/kVAr. Reference Standards IEC60831-1/2, UL N.810, CSA

Overvoltage: 460 V (24h), 510 V (8h), 535 V (30m), 555 V (5m), 600 V (1m), 1410 V (Picco)

Overcurrent: 2In (24h), 3In (30m), 4In (15m), 10In (Picco)

### Switch Disconnecter

N. 1 Switch Disconnectors with door interlock sized 1,5 time the nominal current of PFC Unit as per EN61921, 3\*80 A

### Fuses

NH00 Fuses 100 kA for the protection of each capacitor bank. Auxiliary circuits are protected through 10,3 x 38 Fuses

### Cabinet

Sheet-steel enclosure 15 and 20/10, painted with epoxy dust paint, colour RAL7035 (others on request).

Protection degree IP30 external, IP00 internal (IP20 with open doors on live parts).

Internal wiring made with cables are FS17 type, Reference standards CEI EN 50575, CEI UNEL 35716, CEI EN 50525 e CPR UE305/11.).

<b>Incoming cables</b>	From the Top
<b>Dimensions / Weight</b>	(W*H*D) 304*370*267 mm / 19 Kg
<b>Ventilation</b>	Ventilation Natural