

# g52filter-rack

## || 75 kVAr

### Modular Racks with Detuning Chokes 134 Hz (p=14%)

Code	CFG5275/1							
Rated voltage	400 ÷ 415 V							
Frequency	50 Hz							
Capacitors Voltage	525 V	<b>Vmax</b>	525	580	600	15m	5m	<b>Peak</b>
Capacitors Voltage max	580 V	<b>Imax</b>	3In		4In	5In	630	1600
THDi max	≤ 100 %						680	10 In
Power @ 400 V	75 kvar							
Power @ 415 V	81 kvar							
Rated current	108 A							
Banks (400 V)	75							
Steps	1 x 75 kVAr							
Typology of Capacitors	MKP525G							
Dimensions (WxHxD)	695*300*500							
Reference standards (PFC unit)	EN61921, EN61439-1/2							



#### Technical Features

**Capacitors** Three-phase metallized polypropylene Capacitors with Nitrogen Gas (N<sub>2</sub>) insulation, “dry type”, MKP525G Series, Rated Voltage 525 V, Insulation Voltage 690 V, equipped with discharge resistors, overpressure safety device and IP20 terminals. Dielectric losses < 0,2W/kVAr. Reference Standards IEC60831-1/2, UL N.810, CSA

**Detuning Chokes** made of copper/aluminum sheet oriented crystals, placed in series between the contactor and the capacitor bank, with the following features: linearity 1.8 Ip/In, realized in class H, over temperature range: 60°C, complete with thermal probe for switching off Capacitors Banks in case of overtemperature, limit the peak current inrush capacitors, detuning frequency 134 Hz (p=14%), standard for 5th Harmonic

**Three-Pole Contactors** for capacitor banks, with high number of insertions (>250.000)

– 3-pole mains and 1 built-in auxiliary contact

– block for serial insertion in the circuit of 3 resistors that limit the peak current at the excitation of the condenser battery. Reference standards IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1

**Modular Rack in sheet-steel** 15 and 20/10, equipped with an aluminium busbar system (**TELEGROUP's PFCs are Type Tested KEMA ref. 5189-16 l<sub>cw</sub> 50 kA for 1 sec**). Protection degree IP00. Thanks to the new concept, the access for maintenance is very easy. The wiring is realized through FS17, Standards CEI EN 50575, CEI UNEL 35716, CEI EN 50525 and CPR UE305/11

**NH00 Fuses** 100 kA for the protection of each capacitor bank.