

r52filter

|| 475 kVAr

Automatic Power Factor Correction system with detuning chokes 134 Hz (p=14%)

Code	TLFR52475								
Rated voltage	400 ÷ 415 V								
Frequency	50 Hz	Vmax	24h	8h	30m	15m	5m	1m	Peak
Capacitors Voltage	525 V	Imax	525	580	600				
Capacitors Voltage max	580 V		2In		3In	4In	630	680	1600
THDi max	100 %								10 In
THDv max	< 5 %								
Power @ 400 V	475 kvar								
Power @ 415 V	511 kvar								
Rated current	686 A								
Banks (400 V)	25-50-100-100-100-100								
Steps	19 x 25 kVAr								
Typology of Capacitors	MKP525R								
PFC Controller	PCRL8								
Switch Disconnecter	3x1000 A (Icc 50 kA)								
Input of cables	Bottom								
Dimensions (WxHxD)	1600*1730*600 mm								
Weight	640 Kg								
Temperature class (PFC unit)	-25 / +65°C								
Insulation voltage (PFC Unit)	690 V								
Max overload (PFC unit)	1,3 In								
Total losses (PFC unit)	< 2 W/kvar								
Reference standards (PFC unit)	EN61921, EN61439-1								



Technical Features

Capacitors Three-phase metallized polypropylene Capacitors with Resin insulation, MKP525R Series, Rated Voltage 525 V, Insulation Voltage 690 V, equipped with discharge resistors, overpressure safety device and IP20 terminals. Dielectric losses < 0,2W/kVAr. Reference Standards IEC60831-1/2, UL N.810, CSA

Detuning Chokes made of copper/aluminum sheet oriented crystals, placed in series between the contactor and the capacitor bank, with the following features: linearity 1.8 Ip/In, realized in class H, over temperature range: 60°C, complete with thermal probe for switching off Capacitors Banks in case of overtemperature, limit the peak current inrush capacitors, detuning frequency 134 Hz (p=14%), standard for 3rd Harmonic

Three-Pole Contactors for capacitor banks, with high number of insertions (>250.000)

– 3-pole mains and 1 built-in auxiliary contact

– block for serial insertion in the circuit of 3 resistors that limit the peak current at the excitation of the condenser battery. Reference standards IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1

Automatic PFC Microprocessor Controller PCRL Series, completed with backlit multilingual LCD Display in 6 languages (Ita, Eng, Deu, Fra, Esp, Por), with the following features: Operation on 4 Quadrants for cogeneration systems, Automatic Recognition of the direction of the current, RMS Voltage and Current, Uniform the use of each Bank / Status of each Bank / Weekly Power Factor, Capacitors overload, Overtemperature, Network THD, AUT / MAN, Protection for overcurrent, overvoltage and overtemperature and micro-interruptions, Setting of Maintenance Program/Advise by month/year

Sheet-steel enclosure 15 and 20/10, painted with epoxy dust paint, colour RAL7035 (others on request). Connection through power cables FS17 (CEI EN 50575, CEI UNEL 35716, CEI EN 50525 and CPR UE305/11). Internal setting in Modular Racks connected through aluminium busbar system (**Type Tested KEMA ref. 5189-16 Icw 50 kA for 1 sec.**). Protection degree IP30 external (IP54 on request), IP00 internal (IP20 with open doors on live parts)

Three-pole Switch Disconnecter with door interlock, sized 1,5 time the nominal current of PFC Unit as per EN61921

NH00 Fuses 100 kA for the protection of each capacitor bank. Auxiliary circuits are protected through 10,3 x 38 Fuses

Single phase transformer for separating the power circuit from the auxiliary circuit (220 Vac, others on request).

Ventilation Forced with Fan + Thermostat connected with PFC Controller for alarm signal and switch off contactors in case of overtemperature (natural operation up to 35°C; forced ventilation from 35°C; with a temperature of 50°C, the PFC will be switched off)